

## Thermal Transfer Ribbon – WAX, resin enhanced

## **|| AG13 ||**

### Description:

AG13 is universal wax foil that handles basic general purpose applications with low printing energy. It is designed to handle print speed up to 300 mm/s. It combines sharper, blacker print quality with outstanding print quality for normal and rotated bar codes. Mainly used on logistic labels, coated, and uncoated paper tag to mid-range synthetic films. It has superior print quality on coated labels and enhanced smooth and scratch resistance. AG13 guarantees very good printing quality and it is possible to choose from wide range already silted rolls for different types of thermal transfer printers with flat heads. AG13 is suitable for printers with flat heads such as Avery, Novexx, Zebra, Datamax, Intermec, Citizen, Sato and others.

### Recommended media:

logistic labels  
coated and uncoated paper tags  
Polyethylene films  
Polypropylene films

### Applications:

general purpose labelling  
labels for shipping and warehouse  
companies  
retail labels and tags  
labels for single and multiple packaging  
pharmaceutical labels  
blood bags, polybags, and machinery part  
labels  
very good for small text and objects  
ingredient labels, drum, shelf and  
horticulture

### Technical specifications:

Film Thickness	4,8 microns
Total ribbon thickness	7,9 microns
Transmition density	1,45 MacBeth Scale
Recommended maximum print speed	300mm/s
Solubility in water (20°C)	negligible
Storage	dry location
Extinguishing media	water, foam, dry, chemical, CO2

### Hazardous components:

Ingredients not precisely identified are proprietary or non-hazardous. Therefore, to the best of our knowledge these products do not contain any hazardous components of 1% or greater or carcinogens of 0.1% or greater such as Hg, Cd, Pb, Cr, PBB or PBDE.