

Adresa: IQ PRODUCT s.r.o., Nálepkova 7847/32A,

921 01 Piešťany

Účet: ČSOB

IBAN: SK987500000004026389518

SWIFT: CEKOSKBX

IČO/IČ DPH: 51825163/SK2120808690 Tel: +421 33 77 205 41, 77 205 42

e-mail: <u>info@iqproduct.com</u> url: <u>www.iqproduct.com</u>

Spoločnosť je registrovaná v OR OS Trnava vložka č. 43277/T

Thermal Transfer Ribbon – RESIN, black

|| AG54 ||

Description:

AG54 is premium resin foil that handles general purpose applications with mid-high printing energy – almost like wax-resin energy. It combines sharper, blacker print quality with outstanding print quality for normal and rotated bar codes. Mainly used on plastic labels, various films and synthetic papers. It is designed to handle print speed up to 250 mm/s.AG54 guaranties very good printing quality and it is possible to choose from wide range already silted rolls for different types of thermal transfer printers with flat heads.AG54 is suitable for printers with flat heads such as Avery, Zebra, Datamax, Intermec, Citizen, Sato and near edge heads as well!

Recommended media:

Applications:

retail plastic tags
coated paper
various type of films
PET labels
I
tag paper

plastic identification labels labels for shipping and warehouse companies retail labels and tags abels for single and multiple packaging pharmaceutical labels, blood bags ingredient labels, drum, shelf and horticulture, warning labels

Technical specifications:

Head typeFlat and Near EdgeFilm Thickness $4,5 \mu m \pm 0,5 \mu m$ Total ribbon thickness $6,9 \mu m \pm 0,5 \mu m$ Melting pointnoneHeat registered150°C

Heat resistance 150°C
Storage dry location

Extinguishing media water, foam, dry, chemical, CO2

Typical compliance: Reach-SVHC Free, RoHS,TSCA,Direct Food

Contact

Performance:

testing results on scale 1-5 (5 is the best):

5 – scratch resistant

5 - smudge resistant

4 - chemical resistant

5 – sensitivity

5 - print quality