

Polyamide Tape

|| NTT23 ||

Description:

| | |
|------------------------------------|--|
| Material: | 100% Polyamide tape |
| Manufacturer identification: | NTT23 |
| Hazardous ingredients: | identify information N/A |
| Physical/chemical characteristics: | appearance and odor – clean |
| Coated resin: | polyamide coated nylon taffeta |
| Color: | white |
| Total weight: | 62+/-5 G/SQ |
| Thickness: | 0,113+/- 0,005mm |
| Standard width: | 15, 20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 90, 100mm |
| Length: | 200/400m |

Fire and explosion hazards data:

| | |
|-------------------------------------|--|
| Flashpoint: | N/A |
| Extinguishing media: | water, dry chemical, foam |
| Special firefighting procedures: | use appropriate firm fighting protective equipment including SCBA. Do not breathe smoke. |
| Unusual fire and explosion hazards: | the smoke from combustion may contain hazardous decomposition products. |

Printing method:

wet ink, silk screen, rotary, letter press and excellent offset printing, thermal transfer printing

Reactivity data:

| | |
|------------------|---------------------------------------|
| Stability: | stable |
| Incompatibility: | strong acids, strong bases, oxidizers |
| Water washing: | 60°C |
| Dry Clean: | Yes |
| Stone washing: | No |

Hazardous decomposition products:

It is reasonable to expect that the decomposition products may include toxic materials such as carbon dioxide and carbon monoxide.



Adresa: IQ PRODUCT s.r.o., Nálepková 7847/32A,
921 01 Piešťany
Účet: ČSOB
IBAN: SK9875000000004026389518
SWIFT: CEKOSKBX
IČO/IČ DPH: 51825163/SK2120808690
Tel: +421 33 77 205 41, 77 205 42
e-mail: info@iqproduct.com
url: www.iqproduct.com
Spoločnosť je registrovaná v OR OS Trnava vložka č. 43277/T

Oeko-tex approved:

Oeko-Tex I. Class

Precautions for safe handling and use:

Waste disposal method: material is currently not considered to be a hazardous waste material. Waste Material may be disposed of through routine handling for any sanitary/municipal waste material in accordance with local laws.

Precautions to be taken in handling and storing:

Use it according to good industrial workplace practices. It should be stored in a dry area away from excessive heat.